



# 高速自動封切機

AUTO HIGH-SPEED SEALING & CUTTING MACHINE

# 厚袋專用自動封切機

THICK-BAG AUTOMATIC SEALING & CUTTING MACHINE



MONNET  
SPIRIT

大豐大藥房  
大豐大藥房

KANS  
AIRPO  
INTER  
AL B  
特

# 高速自動封切機

AUTO HIGH-SPEED SEALING & CUTTING MACHINE

## ■可增設裝置：

- 1、加裝自動輸送機裝置。
- 2、可改裝專用製背心袋並自動成疊。
- 3、送料部，可改為兩線分開自動送料。

## ■本機特點：

- 1、主機馬達使用電子式無段控制變速。
- 2、全部採用電子控制以達自動化控制。
- 3、利用電磁式離合器及制動器使封切袋子之尺寸誤差小。
- 4、停車時自動定位。
- 5、摺袋自動停車。
- 6、精密度電眼，自動封切印刷物。
- 7、操作簡便封口牢固。
- 8、高速作業，節省人力時間。

## OPTIONAL ACCESSORIES AS FOLLOWS:

- 1.AUTO CONVEY FEEDING EQUIPMENT.
- 2.IT WILL BE EXCHANGE TO MANUFACTURE VEST SHOPPING BAGS AND AUTO STACK.
- 3.IT WILL BE EXCHANGE TO 2 LINES SORTING & AUTO FEEDING.

## FEATURE:

- 1.MAIN MOTOR IS ELECTRIC CONTROL SPEED.
- 2.FULLY-AUTO ELECTRIC CONTROL SPEED.
- 3.ELECTROMAGNETIC CLUTCH AND BRAKE WHICH ENSURE BAG FOR CUTTING AND SEALING ACCURATE.
- 4.IT WILL BE AUTO SETTING WHEN YOU PUSH THE STOP-BUTTON.
- 5.IT CAN ACCUMULATE BAGS AND AUTO STOP.
- 6.HI-SENSITIVITY ELECTRONIC SENSOR WHICH CAN AUTO SEAL & CUT PLASTIC FILMS.
- 7.EASY OPERATING AND SEAL PERFECTION.
- 8.FAST OPERATING THAT CAN SAVE TIME AND WAGE.

型式 MODEL	切刀寬 CUTTER "W"	裁切長度 CUTTING "L"	每分鐘 P C S/MIN	長度誤差 ACCURACY "L"	封切厚度 CONVERTING THICKNESS	機械長度	機械寬度	機械高度	機械重量 MACHINE WEIGHT	動力 MOTOR	電熱 HEATER	全機需電 POWER REQUIRED	裝箱長度	裝箱寬度	裝箱高度	裝箱重量 GROSS WEIGHT
						L	DIMENSION W	H					L	PACKING W	H	
SDH-264	26"	1"-40"	25-130	±2/1000%	0.015-0.10%	2.55M	1.25M	1.5M	600KG	2P	1.2KW	2.5KW	2.4	1.5	1.65	700KG
SDH-326	32"	1"-60"	25-100	±2/1000%	0.015-0.10%	2.95M	1.45M	1.4M	680KG	2P	1.5KW	4.0KW	2.4	1.65	1.65	850KG
SDH-406	40"	1"-60"	10-80	±2/1000%	0.015-0.10%	2.95M	1.65M	1.7M	750KG	2P	1.8KW	4.5KW	2.4	1.85	1.9	980KG

\* 規格變更不另行通知 Specifications are subject to change due to technological improvement.

## Usable Film Materials

LDPE tube film  
HDPE tube film  
LLDPE tube film



# 厚袋專用自動封切機

THICK-BAG AUTOMATIC SEALING & CUTTING MACHINE

## ■本機特點：

- 1、多片式封刀能使袋子封底更堅固美觀。
- 2、製造較厚之袋子如：手提袋、鹽袋、原料袋、米袋、冷凍袋、菓子袋、巴樂袋、石粒袋、糖袋、螺絲袋、農藥袋等。

## OUTSTANDING QUALITIES:

1. POLY-SEALING KNIVES MAKE THE SEALED FOUNDATION OF THE BAGS FIRM AND PRETTY.
2. TO MANUFACTURE THICK POLY-BAG SUCH AS: HANDBAG, SALT BAG, MATERIAL BAG, RICE BAG, REFRIGERATION BAG, JUJUBE BAG, GUAVA BAG, PEBBLE BAG, SUGAR BAG, SCREW BAG, PESTICIDE BAG, ETC.

型式 MODEL	切刀寬 CUTTER "W"	裁切長度 CUTTING "L"	每分速度 P C S/MIN	長度誤差 ACCURACY "L"	封切厚度 CONVERTING THICKNESS	機械長度	機械寬度	機械高度	機械重量 MACHINE WEIGHT	動力 MOTOR	電熱 HEATER	全台備電 POWER REQUIRED	裝箱長度	裝箱寬度	裝箱高度	裝箱重量 GROSS WEIGHT
						L	DIMENSION W	H					L	PACKING W	H	
SDH-2630	26"	5"-24"	10-70	2/1000%	0.06-0.40%	3.5M	1.00M	1.30M	560KG	2P	1.5KW	3.5KW	3.7M	1.4M	1.80M	780KG
SDH-3260	32"	5"-50"	10-50	"	0.06-0.40%	3.5M	1.15M	1.60M	600KG	2P	1.7KW	4.0KW	3.7M	1.6M	"	850KG

專利新型第一二八九五號  
厚袋膠袋封切機之獨立單件  
聯封口裝置（上下加熱）

PATENT NO 12895- NEW STYLE  
A sealing and cutting machine for thick poly bag offers independent unit of single sealing (heating both upward and downward)



---

世岱工業股份有限公司

S-DAI INDUSTRIAL CO.,LTD.

---

